LAB SETUP AMERICA

PRODUCT CATALOG | FIXTURES & SAFETY EQUIPMENT

Laboratory Fixtures

Faucets, fume hood fittings, pure water fixtures, emergency showers, eyewashes and safety stations



- Laboratory faucets
- Fume hood fittings
- Emergency safety equipment
- www.lsamerica.com

Introduction & Contents

A complete line of laboratory service fixtures and emergency safety equipment — supplied with your casework, fume hoods and worksurfaces by Lab Setup America.

This catalog brings together WaterSaver laboratory fixtures: forged-brass faucets with self-contained compression valve units, combination and pre-rinse fixtures, pure water faucets, remote control fume hood fittings, and a full range of ANSI Z358.1 emergency showers, eyewashes and safety stations.

Forged brass
Durable bodies with color-coded index discs by service.

Factory tested
Every fixture is fully assembled and tested before shipment.

ANSI Z358.1
Emergency equipment third-party certified to comply.

Barrier-free
ADA-compliant safety stations, showers and eyewashes.



CONTENTS

Laboratory Faucets	3
Combination Fixtures	5
Foot-Operated Faucets & Goosenecks	6
Pre-Rinse Units	6
Pure Water Faucets	7
Remote Control Fume Hood Fittings	8
Safety Stations & Accessories	10
Recessed Laboratory Safety Units	11
Emergency Showers	12
Eyewashes & Eye/Face Washes	13
Eyewash / Drench Hose Units	16
Faucet-Mounted Eyewashes	17
Ordering Reference: Service Colors, Remote Assemblies, Spray Heads & Signs	18

Model numbers, specifications and finishes are per manufacturer literature and subject to change. Contact Lab Setup America to confirm options, service, mounting and finish before ordering.

LABORATORY FAUCETS

Deck, panel and wall mounted single and mixing faucets in forged brass, with self-contained compression valve units and vacuum breaker op...



L611VB

Single Faucet, Deck Mounted, Vacuum Breaker

Deck mounted faucet with vacuum breaker for cold water.

Gooseneck: 6" rigid gooseneck.

Body: Forged brass.

Also available: L612VB swing gooseneck; **L614VB** convertible rigid/swing gooseneck



L611VB-BH

Single Faucet, Deck Mounted, Vacuum Breaker and Blade Handle

Deck mounted faucet with vacuum breaker and wrist blade handle for cold water.

Gooseneck: 6" rigid gooseneck.

Body: Forged brass.

Also available: L612VB-BH swing gooseneck; **L614VB-BH** rigid/swing gooseneck



L2714VB-WSA

Single Faucet, Panel Mounted, Vacuum Breaker

Panel mounted faucet with vacuum breaker for cold water.

Gooseneck: 6" rigid/swing gooseneck.

Body: Forged brass.

Also available: L2714L-VB-WSA handle on left side



L412VB

Mixing Faucet, Deck Mounted, Vacuum Breaker

Deck mounted mixing faucet with vacuum breaker for hot and cold water.

Gooseneck: 6" swing gooseneck.

Body: Forged brass.

Also available: L411VB rigid gooseneck; **L414VB** convertible rigid/swing gooseneck



L412VB-BH

Mixing Faucet, Deck Mounted, Vacuum Breaker and Blade Handles

Deck mounted mixing faucet with vacuum breaker and wrist blade handles for hot and cold water.

Gooseneck: 6" swing gooseneck.

Body: Forged brass.

Also available: L411VB-BH rigid gooseneck; **L414VB-BH** convertible rigid/swing gooseneck



L410

Mixing Faucet, Deck Mounted, Swing Spout

Deck mounted faucet for hot and cold water.

Body: Forged brass.

Inlet: 1-3/16" male shank with (2) 3/8" OD flexible copper tubes.

Also available: L410VB vacuum breaker



L2210

Mixing Faucet, Deck Mounted

Deck mounted faucet on 8" centers for hot and cold water.

Body: Brass bar stock.

Inlets: Valves have 1-3/8" male shank with 3/8" OD flexible copper tube inlet.



L2212VB

Mixing Faucet, Deck Mounted, Vacuum Breaker

Deck mounted faucet with vacuum breaker on 8" centers for hot and cold water.

Gooseneck: 6" swing gooseneck.

Body: Brass bar stock.

Also available: L2211VB rigid gooseneck; **L2214VB** rigid/swing gooseneck



L2212TWI-VB-3001

Mixing Faucet, Deck Mounted with Hand/Foot Control

Deck mounted mixing faucet with floor mounted pedal valve.

Gooseneck: 6" swing gooseneck.

Outlet: 3/8" NPS female outlet with removable anti-splash serrated hose end.

Also available: L2211TWI-VB-3001 rigid gooseneck; **L2214TWI-VB-3001** rigid/swing gooseneck



L2210BH

Mixing Faucet, Deck Mounted

Deck mounted faucet on 8" centers for hot and cold water.

Body: Brass bar stock.

Inlets: Valves have 1-3/8" male shank with 3/8" OD flexible copper tube inlet.



L2212VB-BH

Mixing Faucet, Deck Mounted, Vacuum Breaker

Deck mounted faucet with vacuum breaker on 8" centers for hot and cold water.

Gooseneck: 6" swing gooseneck.

Body: Brass bar stock.

Also available: L2211VB-BH rigid gooseneck; **L2214VB-BH** rigid/swing gooseneck



L2212TWI-VB-BH-3001

Mixing Faucet, Deck Mounted with Hand/Foot Control

Deck mounted mixing faucet with floor mounted pedal valve.

Gooseneck: 6" swing gooseneck.

Inlets: Valves have 1-3/8″ male shank with 3/8″ OD flexible copper tube inlet.

Also available: L2211TWI-VB-BH-3001 rigid gooseneck; **L2214TWI-VB-BH-3001** rigid/swing gooseneck

Laboratory Faucets *(continued)*



L2222

Mixing Faucet, Deck Mounted

Deck mounted faucet on 8" centers for hot and cold water.

Gooseneck: 6" swing gooseneck.

Body: Brass bar stock.

Also available: L2221 rigid gooseneck; **L2224** convertible rigid/swing gooseneck



L2222VB

Mixing Faucet, Deck Mounted, Vacuum Breaker

Deck mounted faucet with vacuum breaker on 8" centers for hot and cold water.

Gooseneck: 6" swing gooseneck.

Body: Brass bar stock.

Also available: L2221VB rigid gooseneck; **L2224VB** rigid/swing gooseneck



L2222TWI-3001

Mixing Faucet, Deck Mounted with Hand/Foot Control

Deck mounted mixing faucet with floor mounted pedal valve.

Gooseneck: 6" swing gooseneck.

Outlet: 3/8" NPS female outlet with removable aerator.

Also available: L2221TWI-3001 rigid gooseneck; **L2224TWI-3001** rigid/swing gooseneck



L212VB-WSA

Mixing Faucet, Panel Mounted

Panel mounted faucet for hot and cold water with vertical inlets.

Gooseneck: 6" swing gooseneck.

Body: Forged brass.

Also available: L211VB-WSA rigid gooseneck; **L214VB-WSA** convertible rigid/swing gooseneck



L512VB-WSA

Mixing Faucet, Panel Mounted

Panel mounted faucet for hot and cold water with horizontal inlets on 8" centers.

Gooseneck: 6" swing gooseneck.

Body: Cast brass.

Also available: L511VB-WSA rigid gooseneck; **L514VB-WSA** convertible rigid/swing gooseneck



L1712VB-WSA

Mixing Faucet, Panel Mounted

Panel mounted faucet for hot and cold water with horizontal inlets on 6" centers.

Gooseneck: 6" swing gooseneck.

Body: Cast brass.

Also available: L1711VB-WSA rigid gooseneck; **L1714VB-WSA** convertible rigid/swing gooseneck

COMBINATION FIXTURES

Water plus gas, air or vacuum service from a single deck-mounted fixture.



L66VB-WSA

Double Service Fixture

Deck mounted fixture for cold water and either gas, air or vacuum.

Gooseneck: 6" rigid gooseneck with 3/8" NPS female outlet and removable anti-splash serrated hose...

Base and Valve Body: Forged brass.



L68VB-WSA

Triple Service Fixture

Deck mounted fixture for cold water and gas, air or vacuum.

Gooseneck: 6" rigid gooseneck with 3/8" NPS female outlet and removable anti-splash serrated hose...

Base and Valve Body: Forged brass.



L5300WSA

Double Service Fixture, Heavy Duty

Deck mounted fixture for cold water and either gas, air or vacuum.

Base and Valve Body: Forged brass.

Inlets: Furnished with 3/8" IPS mounting shanks (assembled), locknuts and washers.

Also available: L5300-110WSA L110 in-line vacuum breaker on water outlet



L5400WSA

Double Service Fixture, Heavy Duty

Deck mounted fixture for cold water and either gas, air or vacuum.

Base and Valve Body: Forged brass.

Inlets: Furnished with 3/8" IPS mounting shanks (assembled), locknuts and washers.

Also available: L5400-110WSA L110 in-line vacuum breaker on water outlet



L5800WSA

Double Service Fixture, Heavy Duty, Hot and Cold Water

Deck mounted fixture for hot and cold water and either gas, air or vacuum.


Inlets: Water valve has 1-3/16" male shank with (2) 3/8" OD flexible copper tubes.

Also available: L5800-110WSA L110 in-line vacuum breaker on water outlet

Foot-Operated Faucets & Goosenecks

FOOT-OPERATED FAUCETS & GOOSENECKS

Hands-free floor-mounted foot valves and companion goosenecks.



L3001

Foot-Operated Mixing Valve

Floor mounted foot-operated valve for hot and cold water.

Body: Forged brass with polished chrome plated finish.

Inlets: (2) 1/2" NPT female inlets.

Also available: **L3001LP** extended pedals for ledge mounting



L3050

Foot-Operated Single Valve

Floor mounted foot-operated valve for cold, hot or tempered water.

Pedal: Forged brass pedal mounted on hinged bracket.

Body: Forged brass with polished chrome plated finish.

Also available: **L3050LP** extended pedal for ledge mounting; **L3050TL** tin-lined for use with pure water



L071WSA

Gooseneck, Panel Mounted

Panel mounted gooseneck for use with foot-operated valve.

Gooseneck: 6" rigid gooseneck with 3/8" NPS female outlet and removable anti-splash serrated hose...

Body: Brass bar stock.

Also available: **L072WSA** swing gooseneck; **L074WSA** convertible rigid/swing gooseneck



L081WSA

Gooseneck, Deck Mounted

Deck mounted gooseneck for use with foot-operated valve.

Gooseneck: 6" rigid gooseneck with 3/8" NPS female outlet and removable anti-splash serrated hose...

Body: Brass bar stock.

Also available: **L082WSA** swing gooseneck; **L084WSA** convertible rigid/swing gooseneck

PRE-RINSE UNITS

Spring-supported spray assemblies for glassware washing and cleanup sinks.



PR411

Pre-Rinse Unit, Deck Mounted

Deck mounted pre-rinse unit for hot and cold water.

Pre-Rinse Assembly: Self-closing squeeze valve with rubber-bound spray head, insulated handle and locking...

Body: Forged brass.

Also available: **PR611** cold water only



PR1711WSA

Pre-Rinse Unit, Panel Mounted

Panel mounted pre-rinse unit for hot and cold water.

Pre-Rinse Assembly: Self-closing squeeze valve with rubber-bound spray head, insulated handle and locking...

Body: Cast brass.



PR1020

Pre-Rinse Unit, Deck Mounted

Deck mounted pre-rinse spray unit.

Valve: Forged brass self-closing squeeze valve with insulated handle.

Hose: 8' reinforced PVC hose.

Also available: **PR1020FSH** 8' stainless steel hose

PURE WATER FAUCETS

Tin-lined brass and polypropylene-lined fixtures for distilled, deionized and RO water.



L681

Pure Water Faucet, Deck Mounted, Self-Closing Control

Deck mounted faucet for distilled, deionized or reverse osmosis water.

Gooseneck: 6" rigid gooseneck.

Body: Forged brass.

Also available: L682 swing gooseneck; **L684** convertible rigid/swing gooseneck



L691


Pure Water Faucet, Deck Mounted, Manual Control

Deck mounted faucet for distilled, deionized or reverse osmosis water.

Gooseneck: 6" rigid gooseneck.

Body: Forged brass.

Also available: L692 swing gooseneck; **L694** convertible rigid/swing gooseneck



L2800-131WSA-TL

Pure Water Valve, Deck Mounted

Deck mounted valve for distilled, deionized or reverse osmosis water.

Mounting: Deck mounted turret base with single outlet.

Inlet: Furnished with 3/8" IPS mounting shank (assembled), locknut and washer.

Also available: L2800-132SWSA-TL two valves at 180 degrees



L2784WSA

Pure Water Faucet, Panel Mounted, Self-Closing Control

Panel mounted faucet for distilled, deionized or reverse osmosis water.

Gooseneck: 6" rigid/swing gooseneck.

Body: Forged brass.

Also available: L2784L-WSA handle on left side



L2794WSA


Pure Water Faucet, Panel Mounted, Manual Control

Panel mounted faucet for distilled, deionized or reverse osmosis water.

Gooseneck: 6" rigid/swing gooseneck.

Body: Forged brass.

Also available: L2794L-WSA handle on left side



L5100F-225WSA-TL

Pure Water Valve, Panel Mounted

Panel mounted valve for distilled, deionized or reverse osmosis water.

Mounting: For installation on vertical or horizontal surfaces (such as pipe chases or service...

Inlet: Furnished with 3/8" IPS mounting shank (assembled), locknut and washer.

Also available: L5100FT-325TL adjustable escutcheon for wall



L7833

Pure Water Faucet, Polypropylene-Lined, Deck Mounted

Deck mounted faucet for distilled, deionized or reverse osmosis water.

Inlet: Furnished with 3/8" IPS mounting shank (assembled), locknut and washer.

Outlet: Seven serration plastic hose end.

Also available: L7833SC toggle-style lever handle and self-closing control;



L7834

Pure Water Faucet, Polypropylene-Lined, Panel Mounted

Panel mounted faucet for distilled, deionized or reverse osmosis water.

Inlet: Furnished with 3/8" IPS mounting shank (assembled), locknut and washer.

Outlet: Seven serration plastic hose end.

Also available: L7834SC toggle-style lever handle and self-closing control; **L7834MSC** toggle-style lever handle



L7840

Pure Water Faucet, Polypropylene-Lined, Panel Mounted

Panel mounted faucet for distilled, deionized or reverse osmosis water.

Inlet: Furnished with 3/8" IPS mounting shank (assembled), locknut and washer.

Outlet: Seven serration plastic hose end.

Also available: L7840SC toggle-style lever handle and self-closing control;



L7853

Pure Water Faucet, Polypropylene-Lined, Deck Mounted

Deck mounted faucet for distilled, deionized or reverse osmosis water.

Gooseneck: 6" rigid gooseneck.

Inlet: Furnished with 1-3/16" dia.

Also available: L7853SC self-closing four-arm handle; **L7853SC-LE** self-closing lever handle



L7854

Pure Water Faucet, Polypropylene-Lined, Panel Mounted

Panel mounted faucet for distilled, deionized or reverse osmosis water.

Gooseneck: 6" rigid gooseneck.

Inlet: Furnished with 3/4" IPS mounting shank (assembled), locknut and washer.

Also available: L7854L handle on left side; **L7854SC** self-closing four-arm handle; **L7854SC-LE** self-closing lever



L7837

Recirculating Pure Water Faucet, Polypropylene-Lined, Deck Mounted

Recirculating deck mounted faucet for distilled, deionized or reverse osmosis water.

Inlet: Furnished with 7/8" OD mounting shank (assembled), locknut and washer.

Outlet: Seven serration plastic hose end.

REMOTE CONTROL FUME HOOD FITTINGS

Panel and rod-type remote control valves, outlet fittings and pure-water hood fittings.



L739

Panel Mounted Valve, Angle Face Fume Hood

Panel mounted valve for installation on angle face of hood.

Also available: L739LFCN/L739RFCN Fine control needle valve construction; **L739LN/L739RN** Needle valve construction; **L739LS/L739RS** Steam valve construction



L740

Panel Mounted Valve, Straight Face Fume Hood

Panel mounted valve for installation on straight face of hood.

Also available: L740FCN Fine control needle valve construction; **L740N** Needle valve construction; **L740S** Steam valve construction



L751

Panel Mounted Valve, Straight Face Fume Hood

Panel mounted valve for installation on straight face of hood.

Also available: L751FCN Fine control needle valve construction; **L751N** Needle valve construction; **L751S** Steam valve construction



LPM4200V

Panel Mounted Ball Valve, Straight Face Fume Hood

Panel mounted remote control ball valve for installation on straight face of hood.



L2885

Rod-Type Valve, Straight Pattern

Rod-type straight pattern valve for installation within side wall or underneath deck of hood.

Also available: L2885FCN Fine control needle valve construction; **L2885N** Needle valve construction; **L2885S** Steam valve construction



L3185

Rod-Type Valve, Angle Pattern

Angle pattern valve for installation within side wall of hood.

Also available: L3185FCN Fine control needle valve construction; **L3185N** Needle valve construction; **L3185S** Steam valve construction



L4285H ADA

Rod-Type Ball Valve, Horizontal Mounting

Remote control ball valve for water and gases.

Also available: L4285HLB For mounting on left hand side of hood; **L4285HRB** For mounting on right hand side of hood



L4285V ADA

Rod-Type Ball Valve, Vertical Mounting

Remote control ball valve for water and gases.

Also available: L4285VLB For mounting on left hand side of hood; **L4285VRB** For mounting on right hand



L7750W-PPL

Panel Mounted Pure Water Valve, Straight Face Fume Hood, Polypropylene-Lined

Panel mounted fume hood valve for distilled, deionized or reverse osmosis water.

Valve Unit: Diaphragm-type valve with brass valve stem and bonnet and inert PTFE diaphragm.



L7759W-PPL

Panel Mounted Pure Water Valve, Angle Face Fume Hood, Polypropylene-Lined

Panel mounted fume hood valve for distilled, deionized or reverse osmosis water.

Valve Unit: Diaphragm-type valve with brass valve stem and bonnet and inert PTFE diaphragm.



L7051WSA-PPL

Fume Hood Outlet Fitting, Panel Mounted, Polypropylene-Lined

Panel mounted polypropylene-lined outlet fitting for distilled, deionized and reverse osmosis water.

Body: Brass bar stock body and flange. **Inlet:** Furnished with 3/8″ IPS brass mounting shank (assembled), locknut and washer.

Also available: L7051-7110WSA-PPL polypropylene vacuum breaker



L7052WSA-PPL

Fume Hood Outlet Fitting, Panel Mounted, Polypropylene-Lined

Panel mounted polypropylene-lined outlet fitting for distilled, deionized and reverse osmosis water.

Body: Brass bar stock body and flange. **Inlet:** Furnished with 3/8″ IPS brass mounting shank (assembled), locknut and washer.

Also available: L7052-7110WSA-PPL polypropylene vacuum breaker

Remote Control Fume Hood Fittings

Remote Control Fume Hood Fittings *(continued)*



L7071WSA-PPL

Fume Hood Gooseneck Fitting, Panel Mounted, Polypropylene-Lined

Panel mounted polypropylene-lined gooseneck for distilled, deionized and reverse osmosis water.

Gooseneck: 8″ rigid brass gooseneck with interior polypropylene lining.

Body: Brass bar stock body and flange.

Also available: L7071-7110WSA-PPL polypropylene vacuum breaker



L7081WSA-PPL

Fume Hood Gooseneck Fitting, Deck Mounted, Polypropylene-Lined

Deck mounted polypropylene-lined gooseneck for distilled, deionized and reverse osmosis water.

Gooseneck: 6″ rigid brass gooseneck with interior polypropylene lining.

Body: Brass bar stock body and flange.

Also available: L7081-7110WSA-PPL polypropylene vacuum breaker



L020WSA

Panel mounted flange with straight ten serration hose end

Details: Furnished with 3/8" IPS mounting shank (assembled), locknut and washer.



L021WSA

Molded nylon panel mounted 45 degree angle flange with nylon ten serration hose end

Details: Available colors are black, blue, brown, green, orange, white and yellow.



L022WSA

Panel mounted 45 degree angle flange with ten serration hose end

Details: Furnished with 3/8" IPS mounting shank (assembled), locknut and washer.



L023WSA

Panel mounted 45 degree angle flange with quick connect fitting

Details: Furnished with 3/8" IPS mounting shank (assembled), locknut and washer.



L024WSA

Panel mounted 45 degree angle flange with 1/4" OD compression fitting


Details: Furnished with 3/8" IPS mounting shank (assembled), locknut and washer.



L036WSA

Deck mounted turret 30 degree angle ten serration hose end

Details: Furnished with 3/8" IPS mounting shank (assembled), locknut and washer.



L050WSA

Deck or panel mounted 90 degree angle body with removable anti-splash serrated hose end

Details: 2-1/8" from panel to hose end.



L051WSA

Deck or panel mounted 90 degree angle body with removable anti-splash serrated hose end

Details: 3-1/2" from panel to hose end.



L052WSA

Panel mounted 90 degree angle body with removable anti-splash serrated hose end

Details: 6" from panel to hose end.



L071VB-WSA

Panel mounted body with 6" rigid vacuum breaker gooseneck

Details: Furnished with 3/8" IPS mounting shank (assembled), locknut and washer.

Also available: L074VB-WSA rigid/swing vacuum breaker gooseneck

Remote Control Fume Hood Fittings *(continued)*



L081VB-WSA

Deck mounted body with 6" rigid vacuum breaker gooseneck

Details: Furnished with 3/8" IPS mounting shank (assembled), locknut and washer.

Also available: L084VB-WSA rigid/swing vacuum breaker gooseneck

SAFETY STATIONS & ACCESSORIES

Free-standing combination shower and eyewash stations, modesty curtains and alarms.



SS902 ANSI Z358.1

Safety Station with Eyewash

Combination eyewash and shower safety station.

Shower Head: 10" (254mm) diameter safety orange ABS plastic.

Spray Head Assembly: Two GS-Plus™ spray heads.

Also available: SS902PCC polished chrome plated brass pipe and fittings. SS909 Combination...; **SS909PCC** polished chrome plated brass pipe and



SS991 ANSI Z358.1

Safety Station with Eyewash, All-Stainless Steel

All-stainless steel combination eyewash and shower safety station.

Shower Head: 10" (254mm) diameter stainless steel.

Spray Head Assembly: Two GS-Plus spray heads.

Also available: SS994 Combination eye/face wash and shower safety station with...



SSBF909 ANSI Z358.1 ADA

Safety Station with Eye/Face Wash, Barrier-Free

Barrier-free combination WideArea™ eye/face wash and shower safety station.

Shower Head: 10" (254mm) diameter safety orange ABS plastic.

Spray Head Assembly: Four GS-Plus™ spray heads.

Also available: SSBF994 all-stainless steel construction



SSBF909PCC ANSI Z358.1 ADA

Safety Station with Eye/Face Wash, Barrier-Free, All-Polished Chrome

Polished chrome plated brass barrier-free combination WideArea™ eye/face wash and shower safety station.

Shower Head: 10" (254mm) diameter stainless steel.

Spray Head Assembly: Four GS-Plus™ spray heads.

Safety Stations & Accessories *(continued)*



AP250-015
Modesty Curtain for Horizontal Showers and Safety Stations

Modesty curtain for installation on horizontally mounted emergency showers and free-standing combination safety...

Curtain: White UV-resistant nylon curtain with ring hangers.

Mounting: Furnished complete with stainless steel track, brackets and clamps for mounting on...



AP250-065
Modesty Curtain for Recessed Laboratory Units

Modesty curtain for use with recessed laboratory units, including emergency showers and combination safety stations.

Curtain: White UV-resistant nylon curtain with ring hangers.

Mounting: Stainless steel track assembly mounts on wall around recessed safety unit.



AP275-205
Alarm Unit for Safety Stations, Flashing Light and Horn

Alarm unit for use with free-standing combination safety stations.

Mounting: Furnished with mounting hardware for installation on the vertical pipe of safety station...

Also available: **A275-200** without remote monitoring capability. Flow switch is single pole,...; **A280-200** without remote monitoring capability.

RECESSED LABORATORY SAFETY UNITS

Wall-recessed safety stations, showers and eye/face washes in stainless steel cabinets.



SSBF2150 ANSI Z358.1 ADA
Recessed Safety Station with Drain Pan, Exposed Shower Head

Recessed eye/face wash and shower safety station with ceiling mounted exposed shower head.

Shower Head: 10" (254mm) diameter stainless steel.

Shower Valve: 1" IPS brass stay-open ball valve with stainless steel “panic bar” actuator.



SSBF2160 ANSI Z358.1 ADA
Recessed Safety Station with Drain Pan, Recess Mounted Shower Head

Recessed eye/face wash and shower safety station with ceiling mounted recessed shower head.

Shower Head: 10" (254mm) diameter stainless steel with flanged rim for recessed mounting in ceiling.

Shower Valve: 1" IPS brass stay-open ball valve with stainless steel “panic bar” actuator.



SSBF2170 ANSI Z358.1 ADA
Recessed Safety Station with Drain Pan, Wall Mounted Shower Head

Recessed eye/face wash and shower safety station with wall mounted exposed shower head.

Shower Head: 10" (254mm) diameter stainless steel.

Shower Valve: 1" IPS brass stay-open ball valve with stainless steel “panic bar” actuator.



ESBF670 ANSI Z358.1 ADA
Recessed Emergency Shower, Exposed Shower Head

Recessed emergency shower with ceiling mounted exposed shower head.

Shower Head: 10" (254mm) diameter stainless steel.

Valve: 1" IPS brass stay-open ball valve with stainless steel “panic bar." Pulling bar down...

Recessed Laboratory Safety Units *(continued)*



ESBF671 ANSI Z358.1 ADA

Recessed Emergency Shower, Recess Mounted Shower Head

Recessed emergency shower with ceiling mounted recessed shower head.

Shower Head: 10" (254mm) diameter stainless steel with flanged rim for recessed mounting in ceiling.

Valve: 1" IPS brass stay-open ball valve with stainless steel "panic bar." Pulling bar down...



ESBF672 ANSI Z358.1 ADA

Recessed Emergency Shower, Wall Mounted Shower Head

Recessed emergency shower with wall mounted exposed shower head.

Shower Head: 10" (254mm) diameter stainless steel.

Valve: 1" IPS brass stay-open ball valve with stainless steel "panic bar." Pulling bar down...



FEBF735DP ANSI Z358.1 ADA

Recessed Eye/Face Wash with Drain Pan

Recessed swing-down eye/face wash with drain pan.

Spray Head Assembly: Two FS-Plus™ spray heads mounted on supply arms.

Valve: 1/2" IPS brass plug-type valve with O-ring seals.

EMERGENCY SHOWERS

Ceiling, wall and horizontally mounted emergency showers, including barrier-free models.



ES629 ANSI Z358.1

Emergency Shower, Recess Mounted

Emergency shower for recessed mounting in a finished ceiling or soffit.

Shower Head: 10" (254 mm) diameter stainless steel with flanged rim for flush mounting in ceiling.

Valve: 1" IPS brass stay-open ball valve.



ES658 ANSI Z358.1

Emergency Shower, Semi-Recessed Ceiling Mounted

Emergency shower for semi-recessed mounting in a 8 - 10 finished ceiling.

Shower Head: 10 " (254 mm) diameter stainless steel.

Valve: 1 " IPS brass stay-open ball valve.



ES635 ANSI Z358.1

Emergency Shower, Vertically Mounted

Emergency shower for vertical mounting.

Shower Head: 10 " (254 mm) diameter safety orange ABS plastic.

Valve: 1 " IPS chrome plated brass stay-open ball valve.



ES692 ANSI Z358.1

Emergency Shower, Vertically Mounted, All-Stainless Steel

All-stainless steel emergency shower for vertical mounting.

Shower Head: 10 " (254 mm) diameter stainless steel.

Valve: 1 " IPS stainless steel stay-open ball valve.

Emergency Showers *(continued)*



ES643 ANSI Z358.1

Emergency Shower, Horizontally Mounted

Emergency shower for horizontal mounting.

Shower Head: 10 " (254 mm) diameter safety orange ABS plastic.

Valve: 1 " IPS chrome plated brass stay-open ball valve.



ES691 ANSI Z358.1

Emergency Shower, Horizontally Mounted, All-Stainless Steel

All-stainless steel emergency shower for horizontal mounting.

Shower Head: 10" (254 mm) diameter stainless steel.

Valve: 1 " IPS stainless steel stay-open ball valve.



ESBF643 ANSI Z358.1 ADA

Barrier-Free Emergency Shower, Horizontally Mounted

Barrier-free emergency shower for horizontal mounting.

Shower Head: 10 " (254 mm) diameter safety orange ABS plastic.

Valve: 1 " IPS chrome plated brass stay-open ball valve.



ESBF658 ANSI Z358.1 ADA

Barrier-Free Emergency Shower, Semi-Recessed, Ceiling Mounted

Barrier-free emergency shower for semi-recessed mounting in a finished ceiling.

Shower Head: 10 " (254 mm) diameter stainless steel.

Valve: 1 " IPS brass stay-open ball valve.

EYEWASHES & EYE/FACE WASHES

Deck, wall and countertop mounted units, including AutoFlow™ swing-down designs.



EW808 ANSI Z358.1

Eyewash, Recessed Deck Mounted, Exposed Valve

Eyewash for recessed mounting in countertop.

Spray Head Assembly: Two GS-Plus™ spray heads.

Bowl: 13 " (330 mm) diameter stainless steel with flanged rim for mounting in countertop.



EW810 ANSI Z358.1

Eyewash, Recessed Deck Mounted, Concealed Valve

Eyewash for recessed mounting in countertop.

Spray Head Assembly: Two GS-Plus™ spray heads.

Bowl: 13 " (330 mm) diameter stainless steel with flanged rim for mounting in countertop.



EW814 ANSI Z358.1

Eyewash, Wall Mounted

Eyewash for wall mounting.

Spray Head Assembly: Two GS-Plus™ spray heads.

Bowl: 11-1/2 " (292 mm) diameter stainless steel.



EW814BC ANSI Z358.1

Eyewash, Wall Mounted, Bowl Cover

Eyewash for wall mounting.

Spray Head Assembly: Two GS-Plus™ spray heads.

Bowl: 11-1/2 " (292 mm) diameter stainless steel with bowl cover.

Eyewashes & Eye/Face Washes *(continued)*



EW805 ANSI Z358.1

Eyewash, Deck Mounted, 90 Degree AutoFlow™

AutoFlow™ eyewash for mounting on counter next to sink.

Spray Head Assembly: Two GS-Plus™ spray heads.

Construction: Polished chrome plated brass.



EW895 ANSI Z358.1

Eyewash, Deck Mounted, 90 Degree AutoFlow™, All-Stainless Steel

All-stainless steel AutoFlow™ eyewash for mounting on counter next to sink.

Spray Head Assembly: Two GS-Plus™ spray heads.

Construction: Type 316 stainless steel.



EW806 ANSI Z358.1

Eyewash, Deck Mounted, 90 Degree Swivel

Swivel eyewash for mounting on counter next to sink.

Spray Head Assembly: Two GS-Plus™ spray heads.

Construction: Polished chrome plated brass.



EW893 ANSI Z358.1

Eyewash, Deck Mounted, 90 Degree Swivel, All-Stainless Steel

All-stainless steel swivel eyewash for mounting on counter next to sink.

Spray Head Assembly: Two GS-Plus™ spray heads.

Construction: Type 316 stainless steel.



EW848 ANSI Z358.1

Eyewash, Wall Mounted, 90 Degree AutoFlow™

AutoFlow eyewash for mounting on wall behind sink.

Spray Head Assembly: Two GS-Plus™ spray heads.

Construction: Polished chrome plated brass.



EW898 ANSI Z358.1

Eyewash, Wall Mounted, 90 Degree AutoFlow™, All-Stainless Steel

All-stainless steel AutoFlow™ eyewash for mounting on wall behind sink.

Spray Head Assembly: Two GS-Plus™ spray heads.

Construction: Type 316 stainless steel.



EW849 ANSI Z358.1

Eyewash, Deck Mounted, 90 Degree AutoFlow™

AutoFlow™ eyewash for mounting on counter behind sink.

Spray Head Assembly: Two GS-Plus™ spray heads.

Construction: Polished chrome plated brass.



EW899 ANSI Z358.1

Eyewash, Deck Mounted, 90 Degree AutoFlow™, All-Stainless Steel

Stainless steel AutoFlow™ eyewash for mounting on counter behind sink.

Spray Head Assembly: Two GS-Plus™ spray heads.

Construction: Type 316 stainless steel.



EWBF849 ANSI Z358.1 ADA

Eyewash, Deck Mounted, 90 Degree AutoFlow™, Barrier-Free

Barrier-Free AutoFlow™ eyewash for mounting on counter behind sink.

Spray Head Assembly: Two GS-Plus™ spray heads.

Construction: Polished chrome plated brass.



FE724 ANSI Z358.1

Eye/Face Wash, Wall Mounted

WideArea™ eye/face wash for wall mounting.

Spray Head Assembly: Four GS-Plus™ spray heads.

Bowl: 11-1/2 " (292 mm) diameter stainless steel.



FE727 ANSI Z358.1

Eye/Face Wash, Recessed Deck Mounted

WideArea™ eye/face wash for recessed mounting in countertop.

Spray Head Assembly: Four GS-Plus™ spray heads.

Bowl: 13" (330 mm) diameter stainless steel with flanged rim for mounting in countertop.



FEBF721 ANSI Z358.1 ADA

Eye/Face Wash, Wall Mounted, Barrier-Free

Barrier-free WideArea™ eye/face wash for wall mounting.

Spray Head Assembly: Four GS-Plus™ spray heads.

Bowl: 11-1/2 " (292 mm) diameter stainless steel bowl.

Eyewashes & Eye/Face Washes *(continued)*



FEBF724 ANSI Z358.1 ADA

Eye/Face Wash, Wall Mounted, Barrier-Free

Barrier-free WideArea™ eye/face wash for wall mounting.

Spray Head Assembly: Four GS-Plus™ spray heads.

Bowl: 11-1/2 " (292 mm) diameter stainless steel.



FE774 ANSI Z358.1

Eye/Face Wash, Deck Mounted, 90 Degree AutoFlow™

AutoFlow™ eye/face wash for mounting on counter next to sink.

Spray Head Assembly: Two FS-Plus™ spray heads.

Construction: Polished chrome plated brass.



FE795 ANSI Z358.1

Eye/Face Wash, Deck Mounted, 90 Degree AutoFlow™, All-Stainless Steel

All-stainless steel AutoFlow™ eye/face wash for mounting on counter next to sink.

Spray Head Assembly: Two FS-Plus™ spray heads.

Construction: Type 316 stainless steel.



FE775 ANSI Z358.1

Eye/Face Wash, Deck Mounted, 90 Degree Swivel

Swivel eye/face wash for mounting on counter next to sink.

Spray Head Assembly: Two FS-Plus™ spray heads.

Construction: Polished chrome plated brass.




FE793 ANSI Z358.1

Eye/Face Wash, Deck Mounted, 90 Degree Swivel, All-Stainless Steel

All-stainless steel swivel eye/face wash for mounting on counter next to sink.

Spray Head Assembly: Two FS-Plus™ spray heads.

Construction: Type 316 stainless steel.



FE778 ANSI Z358.1

Eye/Face Wash, Wall Mounted, 90 Degree AutoFlow™

AutoFlow™ eye/face wash for mounting on wall behind sink.

Spray Head Assembly: Two FS-Plus™ spray heads.

Construction: Polished chrome plated brass.



FE798 ANSI Z358.1

Eye/Face Wash, Wall Mounted, 90 Degree AutoFlow™, All-Stainless Steel

Stainless steel AutoFlow™ eye/face wash for mounting on wall behind sink.

Spray Head Assembly: Two FS-Plus™ spray heads.

Construction: Type 316 stainless steel.



FE779 ANSI Z358.1

Eye/Face Wash, Deck Mounted, 90 Degree AutoFlow™

AutoFlow™ eye/face wash for mounting on counter behind sink.

Spray Head Assembly: Two FS-Plus™ spray heads.

Construction: Polished chrome plated brass.



FE799 ANSI Z358.1

Eye/Face Wash, Deck Mounted, 90 Degree AutoFlow™, All-Stainless Steel

All-stainless steel AutoFlow™ eye/face wash for mounting on counter behind sink.

Spray Head Assembly: Two FS-Plus™ spray heads.

Construction: Type 316 stainless steel.

EYEWASH / DRENCH HOSE UNITS

Dual-purpose eyewash/drench hoses and drench hose units for deck or wall mounting.



EW1022 ANSI Z358.1

Eyewash/Drench Hose Unit, Deck Mounted

Dual purpose eyewash/drench hose unit meets the provisions of ANSI Z358.1-2014 as both an eyewash and a drench hose.

Spray Head Assembly: Two GS-Plus™ spray heads mounted side-by-side.

Valve: Forged brass squeeze valve activated by stainless steel lever handle.



EW1026 ANSI Z358.1

Eyewash/Drench Hose Unit, Wall Mounted

Dual purpose eyewash/ drench hose unit meets the provisions of ANSI Z358.1-2014 as both an eyewash and a drench hose.

Spray Head Assembly: Two GS-Plus™ spray heads mounted side-by-side.

Valve: Forged brass squeeze valve activated by stainless steel lever handle.



EW1041 ANSI Z358.1

Eyewash/Drench Hose Unit, 45 Degree Panel Mounted

Dual purpose eyewash/ drench hose unit meets the provisions Z358.1-2014 of ANSI as both an eyewash and a drench hose.

Spray Head Assembly: Two GS-Plus™ spray heads mounted side-by-side.

Valve: Forged brass squeeze valve activated by stainless steel lever handle.



EW1046 ANSI Z358.1

Eyewash/Drench Hose Unit, Wall Mounted

Dual purpose eyewash/ drench hose unit meets the provisions of Z358.1-2014 ANSI as both an eyewash and a drench hose.

Spray Head Assembly: Two GS-Plus™ spray heads mounted side-by-side.

Valve: Forged brass squeeze valve activated by stainless steel lever handle.



EW1020 ANSI Z358.1

Drench Hose Unit, Deck Mounted

Drench hose unit for deck ANSI Z358.1-mounting.

Valve: Forged brass squeeze valve activated by stainless steel lever handle.

Hose: 8' reinforced PVC hose.

Also available: EW1020BP in-line dual check backflow preventer for installation on inlet of...



EW1025 ANSI Z358.1

Drench Hose Unit, Wall Mounted

Drench hose unit for wall ANSI Z358.1-mounting.

Valve: Forged brass squeeze valve activated by stainless steel lever handle.

Hose: 8' reinforced PVC hose.

Also available: EW1025BP in-line dual check backflow preventer for installation on inlet of...

FAUCET-MOUNTED EYEWASHES

EyeSafe™ units that add supplemental eyewash capability to any sink faucet.



EW100

EyeSafe™ Faucet-Mounted Eyewash

Faucet-mounted eyewash for sink faucets.

Valve: Forged brass diverter valve.

Inlet: 55/64"-27 Body has female thread.



EW101

EyeSafe™ Faucet-Mounted Eyewash

Faucet-mounted eyewash for gooseneck-style faucets.

Valve: Forged brass diverter valve.

Inlet: 55/64"-27 Body has female thread.



EW200

EyeSafe™ Faucet-Mounted Eyewash with Faucet Control Valve

Faucet-mounted eyewash for sink faucets.

Eyewash Valve: Forged brass diverter valve.

Inlet: 55/64"-27 Body has female thread.



EW201

EyeSafe-X™ Faucet-Mounted Eyewash with Faucet Control Valve

Faucet-mounted eyewash for gooseneck-style faucets.

Eyewash Valve: Forged brass diverter valve.

Inlet: 55/64"-27 Body has female thread.

SERVICE INDEX COLORS

Outlet fittings are brass with a powder-coated finish, color-coded to match the fixture service index color.


Service	Color
Air	Orange
Argon	Violet
Carbon Dioxide	Pink
Cold Water	Green
Deionized Water	White
Distilled Water	White
Gas	Blue
Hot Water	Red
Hot/Cold Water	Dark Gray
Hydrogen	Pink
Nitrogen	Brown
Oxygen	Lt. Green
Special Gas	Lt. Blue
Steam	Black
Vacuum	Yellow

ORDERING REMOTE CONTROL ASSEMBLIES

1. Select the remote control valve (L739, L740, L751, LPM4200V, L2885, L3185, L4285H or L4285V). Specify valve construction — suffix **FCN** fine control needle, **N** needle, **S** steam, **W** water or **WTL** tin-lined water — and the service (cold water, gas, air, vacuum, etc.).
2. For L739, LPM4200 and L4285 valves, specify right hand or left hand mounting.
3. Select the outlet fitting. Fittings are furnished with a color-coded epoxy finish as standard.
4. For rod-type valves specify the **"L" dimension** (index disc to valve centerline, 20" standard), the **"Y" dimension** (valve centerline to back of outlet flange, 2-3/4" standard) and guide plate: **PA** flat with screws, **PB** threaded with locknut, **PC** 45° angle, **PD** press-in bushing.

Lab Setup America will confirm the complete assembly number from the manufacturer's valve/outlet ordering tables.

SPRAY HEADS



Soft, full spray from 30 to 100 PSI; polypropylene construction; integrated flip-top dust cover; 60 PPI polyurethane filter; 1.8 GPM (GS-Plus™) or 3.2 GPM (FS-Plus™) flow control.

GS-Plus™ part	Description	FS-Plus™ part
AP470-001W	Spray head, complete	AP470-021W
AP470-002W-R	Dust cover & cap assembly (pkg of 2)	AP470-022W-R
470-004R	60 PPI polyurethane filter (pkg of 6)	470-024R
470-005R	Flow control, 1.8 GPM (GS) / 3.2 GPM (FS) (pkg of 6)	470-025R

EMERGENCY SIGNS — 8-1/2" × 11" plastic

Part number	Sign	Part number	Sign
250-009W	Emergency Shower	250-006W	Emergency Drench Hose
250-007W	Emergency Eyewash	250-008W	Emergency Shower/Eyewash
250-010W	Emergency Eyewash/Drench Hose	250-012W	Emergency Shower/Eyewash (recessed station)

LAB SETUP AMERICA

Fixtures, furniture and fume hoods — from one source

Lab Setup America supplies laboratory casework, fume hoods, worksurfaces, service fixtures and emergency safety equipment — backed by more than 40 years of combined experience. Send us your drawings and fixture schedule for a complete quotation.

CALL	EMAIL	VISIT
801-435-3167	estimating@lsamerica.com	7533 Center View Ct., Ste N West Jordan, UT 84084

www.lsamerica.com

LAB DESIGN & SPACE PLANNING · CASEWORK · FUME HOODS · FIXTURES · INSTALLATION

WaterSaver®, AutoFlow™, EyeSafe™, GS-Plus™ and FS-Plus™ are trademarks of WaterSaver Faucet Co. Product data per manufacturer published literature; specifications subject to change without notice. © 2026 Lab Setup America.